



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 1 of 35

UK Aerospace Youth Rocketry Challenge 2007 Team Handbook



Final Version
November 3rd, 2006

WWW.UKAYRoC.org.uk



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 2 of 35

HANDBOOK

- Section 1. Introduction.
- Section 2. Event Rules
- Section 3. Rocket Design
- Section 4. Rocket Construction
- Section 5 Rocket Flying
- Section 6 Qualifying and Practice Flights
- Section 7. Resources
- Appendix 1. Recommended Schedule of Team Activities
- Appendix 2. UKRA Model Rocket Safety Code
- Appendix 3. List of UKAYROC-Approved Model Rocket Motors
- Appendix 4. Perfectflite Maximum Altitude Altimeter
- Appendix 5. Civil Aviation Authority NOTAM Procedures
- Appendix 6. UKRA Rocket-Flying Insurance Frequently-Asked Questions
- Appendix 7. UKRA Handout on Rocketry Safety



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 3 of 35

Section 1. INTRODUCTION

The UK Aerospace Youth Rocketry Challenge (UKAYROC) provides secondary school students a realistic experience in designing a flying aerospace vehicle that meets a specified set of mission and performance requirements. Students work together in teams the same way aerospace engineers do. It is not intended to be easy, but it is well within the capabilities of secondary school students with a good background in science and math and some craftsmanship skills.

The purpose of the Challenge is to design and build a safe and stable model rocket flight vehicle and use it to lift a fragile payload (one raw hen's egg) to an altitude of exactly 850 feet and also for a total flight duration score of exactly 45 seconds, then return this payload safely and undamaged. Why feet and not meters? By international convention all air users measure altitude in feet.

- Models must weigh no more than 1.5 kg (3.3 pounds) at liftoff and must use commercially-made, UKRA safety-certified model rocket motors with no more than 0.0625 kg (62.5 grams) propellant weight each and a maximum combined propellant weight of no more than 0.125 kg (125 grams).
- Times will be determined by two observers on the ground with electronic stopwatches; time is measured from the moment of liftoff until the moment the egg lands.
- Altitudes will be determined by the official electronic altimeter for the event, the Perfectflite ALT 15K/WD, which must be carried in the model rocket
- Winner is the team whose flight vehicle egg payload comes closest to exactly 850 feet altitude and 45 seconds flight duration score in a safe and stable flight, and returns the egg undamaged -- in a single attempt -- at a "fly-off" hosted in Charterhouse School on April 13, 2007.

The Team Handbook provides the Challenge rules plus some guidelines on how to approach the process of rocket design and flight. It also provides additional sources of information on general model rocket design, construction, and flying. It is not a "cookbook"; no completed design is provided as an example. The challenges and the learning for each team come from developing and testing your own completely original design.

Teams should begin the Challenge by becoming familiar with the basics of model rocketry. Those who have no experience with how these models are built and flown should begin by reading G. Harry Stine's Handbook of Model Rocketry (available from Amazon) and by purchasing, building, and flying a basic model rocket kit, available from many model shops or the vendors listed in Section 7, "Resources".



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 4 of 35

If you live near one of the UKRA affiliated clubs, or near experienced members of the UKRA who have volunteered to be mentors, you are encouraged to consult with them. The clubs are listed at the UKRA web site, WWW.UKRA.ORG.UK. The list of mentors is in the Youth Rocketry section of the UKRA web site. These rocketeers can help teach you the basics of how to build and fly a payload-carrying rocket. Typically they can also help you in locating a test-flying launch sites and notify the Civil Aviation Authority (CAA) of the launch. Many will allow you to do your practice or "qualification" flight at one of their already-organized launches (launch dates and locations also listed at the UKRA web site).

Remember neither these "experts" nor any other adult can help you design, build or fly your actual entry. All of this work must be done by the student members on your team.

If model rocketry interests you and you want to be connected to the rest of the people in the UK who are part of the hobby's "expert team," you should join the UK Rocketry Association. You can do this online at www.UKRA.org.uk or by filling out the membership application forwarded to each team. Membership brings you insurance coverage and a whole range of other benefits and resources. Good luck! Design carefully, fly safely, and we hope to see you at the fly-off in April 2007!



Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 5 of 35

Section 2.

2007 Event Rules

1. **SAFETY.** All rockets must be built and flown in accordance with the Safety Code of the UK Rocketry Association (UKRA) - <http://www.ukra.org.uk/safety.html>. Rockets flown at the fly-off must have previously flown successfully. They will be inspected before launch and observed during flight by an event official, whose judgement on their compliance with the Safety Code and with these rules will be final. Teams are encouraged to consult with designated UKRA officials who are running this event well before the fly-off to resolve any questions about design or flight safety, about the Safety Code, or about these rules.
2. **TEAMS.** No more than three teams may be entered by any sponsoring organization. The application for a team must come from a single school or a single UK incorporated non-profit youth organization (excluding UKRA or any other rocket club or organization). Team members must be students who are currently enrolled in grades 7 through 13 in a UK school. Teams may have members from other schools or other organizations and may obtain financing from any source, not limited to their sponsoring organization. Teams must be supervised by an adult approved by the principal of the sponsoring school, or by an officially-appointed adult leader of their sponsoring youth organization. Minimum team size is three students and maximum is five students. Each student member must make a significant contribution to the designing, building, and/or launching of the team's entry. No part of any of these may be done by any adult, by a company (except by the sale of standard off-the-shelf components available to the general public, but not kits or designs for the event), or by any person not a student on that team. No student may be on more than one team. The supervising teacher/adult may supervise more than one team. The Team International Rocketry Challenge is open to the first teams that submit a completed application, including payment, postmarked no later than November 15, 2006.
3. **ROCKET REQUIREMENTS.** Rockets may be any size, but must not exceed 1500 grams (3.3 pounds) gross weight at liftoff. They may not be commercially-made kits designed to carry egg payloads. They must be powered only by commercially-made model rocket motors that have 62.5 grams or less of propellant each. Any number of motors may be used, but the motors used must not contain a combined total of more than 125 grams (4.4 ounces) of propellant, based on the propellant weights in this List. Loose black powder, separate from the certified rocket motors and their internal ejection charges, may not be used in rockets.
4. **PAYLOAD.** Rockets must contain and completely enclose one raw large hen's egg of 57 to 63 grams weight and a diameter of 45 millimetres or less, and must return this from the flight without any cracks or other external damage. An egg will be issued to the team by event officials during finals, but teams must provide their own egg for their qualifying flights. Rockets must be allowed to land at the end of its flight without human intervention (catching) and will be disqualified if there is such intervention. The egg must be removed from the rocket at the end of the flight in the presence of a designated UKRA event official observer and presented to that official, who will inspect it for damage. Any external damage to the egg is disqualifying.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 6 of 35

6. **DURATION SCORING.** Scores shall be based on total flight duration of the portion of the rocket containing the egg, measured from first motion at liftoff from the launch pad until the moment of landing or until the rocket can no longer be seen due to distance or to an obstacle. Times must be measured independently by two people not on the team, one of whom is the official UKRA-member adult observer, using separate electronic stopwatches accurate to 0.01 seconds. The official duration will be the average of the two times, rounded to the nearest 0.01 second. If one stopwatch malfunctions, the remaining single time will be used. Duration scores will be computed by taking the absolute difference between 45 seconds and the measured average flight duration to the nearest 1/100 second (this difference is always a positive number, or zero).

7. **ALTITUDE SCORING.** Rockets must contain the commercial electronic altimeter (Perfectflite Model ALT 15K) approved for use in this event, in a compartment that is properly vented to the atmosphere. The altimeter must be inspected by an event official both before and after the flight, and may not be modified in any manner. The altimeter must be confirmed by this official to have reset to zero before flight. The altitude of the portion of the rocket containing the egg, as recorded by this altimeter, will be the sole basis for judging the altitude score. This score will be the absolute difference between 850 feet and the altimeter-reported altitude (this difference is always a positive number, or zero).

8. **FLIGHTS.** Team members cannot be changed after the first qualification flight. Only team members on record at Space Connections with valid parent consent forms are eligible to receive prizes. Only one flight is allowed per team at the final fly-off, except as specifically noted in these rules. In order to be eligible for the fly-off, a team is required to fly a qualifying flight observed in person by an adult (senior) member of the UKRA (unrelated to any team members and not a paid employee of their school or member of their youth group) between September 6, 2006 and April 8, 2007. Each team may conduct a maximum of two qualification flights. A second qualification flight is not required if the team is satisfied with the results of their first one. A qualification flight attempt must be declared to the UKRA observer before the rocket's motor(s) are ignited. Once an attempt is declared, the results of that flight must be recorded and submitted to Space Connections, even if the flight is unsuccessful. A rocket that departs the launch pad under rocket power is considered to have made a flight, even if all motors do not ignite. If a rocket experiences a rare "catastrophic" malfunction of a rocket motor (as determined by a UKRA official observer), a replacement flight may be made, with a replacement vehicle if necessary. Flights which are otherwise fully safe and qualified but which result in an altimeter reading of greater than zero feet but less than 50 feet will be counted as "no flight" due to false triggering of the altimeter and may be reflown without penalty. The results from qualification flight attempts must be faxed to and received at the offices of Space Connections by 5pm on Monday, 26th March 2007. As soon as we receive your qualifying score, "Qualification Score Received" will appear under your team information on the "Registered Teams" page at www.UKAYRoC.org.uk. The top-scoring 3 teams will be notified no later than Friday 30th March 2007, and invited to participate in the final fly-off to be held on Friday April 13, 2007 (alternate fly-off date in case of inclement weather will be Saturday April 14, 2007).

9. **SAFE RECOVERY.** Each part of the rocket, including each stage if more than one is used, must either contain a recovery device or be designed to glide, tumble unstably, or otherwise return



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 7 of 35

to earth at a velocity that presents no hazard. Any entry which has a major part (including but not limited to a stage or an expended engine casing) land without a recovery system (gliding/tumbling stages are considered to have a system), or at a velocity that is judged by an event official to be hazardous, due to recovery system absence, insufficiency, or malfunction, will be disqualified.

10. **RETURNS.** Return of the portion of the flight vehicle containing the egg is required by the deadline time established at the beginning of the day's flying. Entries whose egg is not returned after flight by the time deadline cannot receive prizes. If this portion cannot be returned after an otherwise safe and stable flight because it landed in a spot from which recovery would be hazardous (as determined by an event official), a replacement vehicle may be substituted for a second flight. There will be no third flights. Return of the other portions of the rocket is required only if there is a question from an event official concerning the safe operation of the vehicle (e.g. a question as to whether the vehicle ejected a part that landed in an unsafe manner). An entry which has any such portion that is not returned when its return is required for this safety inspection shall be disqualified.

11. **LAUNCH SYSTEMS.** Teams may use the electrical launch system and the launch pads (with six-foot long, 1/4-inch diameter rods) provided by the event officials at the fly-off, or may provide their own system. Systems provided by teams for their own use must be inspected for safety by an event official before use, and must provide at least 6 feet of rigid guidance, including use of a rod diameter of at least 1/4 inch, if a rod is used. All launches will be controlled by the event Range Safety Officer and must occur from the ground.

12. **FREE FLIGHT.** Rockets may not use an externally-generated signal such as radio or computer control (except GPS navigation satellite signals) for any purpose, including flight termination, after liftoff. They may use autonomous onboard control systems to control any aspect of flight.

13. **PLACES.** Places in the competition will be determined on the basis of how close the portion of the entry containing the egg comes to the designated target duration of 45 seconds and the designated target altitude of 850 feet, as determined by the sum of the altitude and duration scores above; the lowest combined score wins. Entries which are disqualified for reasons noted in these rules may not receive a place. Ties will result in pooling and even splitting of the prizes for the affected place(s) - for example, a two-way tie for 2nd place would result in a merger and even division of the prizes for 2nd and 3rd places. The organisers reserve the right to make all last and final contest determinations.



Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 8 of 35

Section 3. ROCKET DESIGN

Because of the size of the payload (the large hen's egg must weigh between 57 to 63 grams and requires the inside of the rocket body to be a diameter of at least 45 millimeters), rockets entered in this Challenge will be fairly large and heavy. The minimum liftoff weight is probably about 0.15 kg, but there is no need for the rocket to be the minimum weight; a larger rocket is also fine, but it will require larger rocket motors.

Designing a rocket that will reach an altitude of approximately 850 feet and stay up approximately 45 seconds is not particularly hard to do, although designing one that cushions and protects an egg is a bit harder. The Challenge is finding the exact combination of airframe design, rocket engines, and duration-control technique that will achieve exactly 850 feet and 45 seconds. Doing this will require either lots of trial-and-error (not recommended), or smart use of a rocket-design and flight-simulation computer program to get the design "roughly right" first. Modern aerospace engineers do lots of "flight tests" on a computer before they start building and flying hardware--it's quicker and cheaper!

How do you approach the process of designing a flight vehicle? Engineers start with what is a fixed, given quantity -- such as the size and shape of the egg payload and its cushioning and the altimeter -- and with what the mission performance requirements are. In this case the requirement is to go to 850 feet and stay up for exactly 45 seconds, then make a safe return to earth at the end. No matter what your design, it must incorporate this payload and achieve the performance requirement.

Remember that this event is about teamwork; engineers design in teams because complex projects that are due in short periods of time demand some kind of division of labour. There are many ways to divide the labour -- perhaps one person could become expert in computer flight-simulation programs, another in the craftsmanship techniques of model rocket building, a third in launch system design, and a fourth in charge of fundraising. All the members need to meet and communicate regularly, because what each one does affects how all the others approach their part of the job. You will need to elect or appoint a Program Manager to make sure everything fits together at the end so that your complex system will work in flight test. And you need to start early!

What, then, are the variables in your aerospace system's design? Well, the size and shape of the rocket certainly has a wide range of possibilities, subject to the overall limitations that the rocket must be safe and stable, and must not exceed 1.5 kg in weight. And the selection of the vehicle's rocket motors is another major variable. Since certified commercially made model rocket motors (those with 0.0625 kg (62.5 grams) and less of propellant each) must be used, you must pick which ones you plan to use from the "Approved Motor List" posted (and updated) at the UKRA website at www.UKRA.org.uk and in Appendix 3. The list of certified motors is quite long, so there is a wide range of possibilities here as well.



Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 9 of 35

There are other design variables to be considered including: what recovery system to use; how to predict or control flight duration in various weather conditions; how to cushion and protect the fragile egg; and what kind of electrical launching device to use.

What all of this means is that, like all engineers, you must engage in an "iterative" design process. You start with a very rough design, evaluate its performance against the requirements, and change the design progressively until your analysis shows that you have a design that is likely to meet them. Then you build, test, evaluate the success or failure of the test, and adjust the design as required until your analysis and tests show that the performance requirement is approximately met. Initial tests are best done as "virtual" flights on a computer, with the time-consuming construction and relatively expensive flight testing of an actual rocket saved for the second step.

Here is a path that you may wish to follow to take you through the design process, along with some additional explanation of the design implications of rocketry terminology used in the event rules and in the UKRA Safety Code.

1. **Accommodate the Payload.** Determine what size compartment is required to contain the altimeter and (separately) a Grade 'A' large egg (maximum diameter 45 millimeters) and cushion them against the shocks of rocket launch, recovery system deployment in flight, and impact with the ground at the end of flight. If you have a flight-termination system that may lead to the egg landing at higher (but still safe) speeds, this requires more egg cushioning.

Hint: Make sure you cushion the egg from impact with the walls of the payload compartment or metal hardware in every direction including the sides when the rocket's parachute snaps open.

2. **Accommodate the Instrumentation.** The electronic altimeter specified for the event must be used in your rocket, and will be the sole basis for measuring the rocket's achieved maximum altitude. You may install other additional altimeter-based systems if you wish, to control "drogue then main" parachute deployment, but only the official altimeter can be used for the official record of achieved altitude. It is very important that the compartment in which the altimeter is placed be properly positioned on the rocket and vented with holes as described in Appendix 4, so that the air pressure inside it is always at equilibrium with the outside air pressure. The instrument measures altitude on the basis of the air pressure changes it senses during flight.

Hint: Place the altimeter in a compartment that is totally sealed on the bottom against intrusion by high-pressure gases from the rocket motor's ejection charge. These gases will make the altitude reading inaccurate.

Hint: Place the altimeter compartment well away from the egg compartment. Turbulent flow over the rocket's nose cone-body tube joint at the top of the rocket (where the eggs are located) will introduce pressure fluctuations for a few inches down the body tube and this



Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 10 of 35

will make the altimeter readings unreliable if it is placed in these first few inches behind the egg compartment

Hint: Secure the altimeter in place mechanically in its compartment, don't let it "rattle" around or rely on foam padding to hold it in place (such padding might interfere with proper pressure equalization of the compartment, anyway). But make it easy to remove, because you will have to remove the altimeter both before and after flight for inspection by event officials.

3. **Decide on Duration-Control Approach.** There are two fundamental paths you can take to try to achieve precise flight duration: fly without an onboard autonomous control system or fly with such a system. Remember that the rules prohibit the use of external man-in-loop controls like radio-control signals that you send to the rocket once it is in flight. The basic tradeoff is between the altitude the rocket flies to and the sink rate (in feet per second) after the recovery system deployment at apogee (maximum altitude). This is based on the size and shape of the parachute or other recovery system you select. This tradeoff can be initially simulated on a computer.
 - a. Free Flight. If you choose the free-flight route (no control system), then the flight vehicle can be fairly simple but you must develop a more complex strategy for adjusting the rocket's recovery system size, shape, etc. before flight in response to the weather conditions at that time. And you will have to do a larger number of practice flights to "calibrate" your adjustments.
 - b. Control. If you choose the more complex control route, you need to decide what form of time or altitude-based control system you plan to use, and what you plan to have it do. If it is a device that triggers an igniter to burn through some number of parachute shroud lines, for example, then where do you plan to install the device in the rocket, how do you initiate it, and how do you plan to attach the parachute so it does not simply "cut away" completely and leave the egg capsule in an unsafe free-fall? These factors will significantly determine the shape and arrangement of your rocket.
4. **Learn to use a rocket-design computer program.** Such a program is the best way to work through the remaining steps of flight vehicle design on a basis other than trial-and-error. There are two good rocket-design programs currently available on the market: SpaceCAD and RockSim, both available to UKAYROC fliers at a discount. There is no single "right" design for this Challenge; there are many different combinations of motor types, rocket length and diameter, rocket weight, and recovery system size and shape that could lead to a flight altitude of 850 feet and flight duration of 45 seconds. A computer program will let you work through the rough possibilities fairly quickly and discard approaches that simply will not work or designs that are not aerodynamically stable. No simulation, however, is exactly accurate. Its estimate of the aerodynamic drag forces on your rocket may be off due to your construction techniques; the rocket motors you use may perform slightly differently from the notional data for them in the program due to normal manufacturing variations, etc. Just because even the best simulation says your rocket will go a specific altitude and then descend at a specific speed under



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 11 of 35

parachute does not mean that it will, exactly. It may go to a lower altitude (usually simulations over-estimate the achieved altitude) and descend more quickly because a parachute shroud line got tangled during its deployment. Or it may crash because of a reliability problem such as how you attached the shock cord! That's why you still need to (and are required to) test-fly at the end of the design process.

5. **Simplicity.** The more complex you make your rocket design, the more things it has that can go wrong and the more it will cost both to develop and test. In the real world of engineering, low cost, rapid delivery, and high reliability is what the customer wants. In this Challenge, since you only get one flight attempt at the fly-off, whatever you fly has to work the first time.

Add complexity (such as clustered rocket motors, staging, etc.) only where you need to in order to meet performance requirements. It may turn out that you need to use one or more of these, but don't assume so from the start.

6. **Basic design safety.** First and foremost, your rocket must be "stable". Read the Handbook of Model Rocketry chapter on stability if you do not know what this means, and use a computer program to calculate stability if in doubt. Because your rocket will be nose-heavy as a result of the egg and altimeter, you should not need extremely large fins -- be conservative and design for a stability margin of at least two "calibers" (Center of Gravity ahead of Center of Pressure by at least two body tube diameters). Second, make sure that the motor(s) you pick provide enough thrust to give your size/weight rocket a speed of 15 m/s or so by the time it reaches the end of its launcher, so that it does not "stagger" slowly into the air and tip over and fly non-vertically if there is any wind. Generally, you need a motor or combination of motors whose combined average thrust is at least five times the rocket liftoff weight. As a rule of thumb, make sure that the model's motors' combined average thrust (in units of Newton's, which is how these are marked on the engine casing) is at least 10 times the rocket's liftoff weight in kg. And finally, plan on using a launch rod of at least 2m in length and 6mm in diameter or a rail for flying these heavy rockets -- they will need the length to achieve safe speed and the rigidity to avoid "rod whip" when the heavy rocket is at the end of the launch rod on its way up.

Electronic parachute deployment systems, if you choose to use them, must be SAFE. If they are designed to sense acceleration or deceleration of the rocket as the basis for starting an ignition or ejection sequence, then there is a great risk that they can trigger on the ground or in your hands if you drop or jog the rocket while carrying it.

Such systems must have a power switch, plug, or other electrical disconnect mechanism that permits you to maintain them in a completely "safe" configuration until placed on the launching pad, and will not be allowed to fly if they do not.

7. **Commercial vs Custom Parts.** The flight vehicle must be made by the student team members. You may use commercially-available "off the shelf" component parts (body tubes, nose cones, egg capsules, etc.) and may adapt some kinds of rocket kits for the event, or you can scratch-



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 12 of 35

build components if you prefer. You may not adapt kits that were specifically designed to carry egg payloads, however. If a company should release a kit or design specifically for the UKAYROC event (none has, so far) you would not be allowed to use such a kit or design. Having a custom flight vehicle part fabricated by a composite or plastics company or custom wood machining company (even if it is to your design) does not constitute sale of a "standard off the-shelf product" and is not allowed. However, having a mandrel fabricated to your specifications that is used to wrap fiberglass on to make your rocket body would be OK. In this case, the company is making a tool; you are making the part that flies.

8. **Metal Parts.** You may only use non-metal parts for the nose, body, and fins of your rocket, those parts that are the main structure of the vehicle. Fiberglass is OK. You may use miscellaneous metal hardware items such as screws, snap links, engine hooks, electronic circuit boards, and (if you wish) commercial re-loadable metal rocket engine casings.

10. **Recovery.** Your rocket may be recovered in several separate sections if you wish. Each section or piece of the rocket must come down safely. A heavy piece (booster stage, nose cone, body section, rocket engine casing, etc.) that falls to earth in a stable, non-tumbling/non-gliding mode at high speed without a recovery system of some kind (parachute, streamer, etc.) is not safe, and flights that have this happen will be disqualified for being unsafe. You cannot have a flight-control system that completely cuts away the recovery system from your egg capsule at a predetermined time and causes it to free-fall to the ground with no recovery device from that point; this is not safe. Normally the only part that must be returned to the event officials after the flight is the part with the egg and altimeter.



Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 13 of 35

Section 4. ROCKET CONSTRUCTION

Designing a rocket on a computer is important, but in the end you have to actually build it right for it to fly the way the computer says it will. There are two key resources available to you for learning the craftsmanship techniques for building a model rocket for UKAYROC: One is the instructional DVD on rocket building provided to each new 2007 UKAYROC team, the other resource is the Handbook of Model Rocketry by G. Harry and Bill Stine, which can be purchased separately from Amazon or some UK rocketry vendors. Watch the DVD and read the applicable chapters of the book before you start trying to put together your rocket. Then build and fly a simple rocket kit before you build your UKAYROC entry.

There are many aspects to constructing a rocket, and this section will not review everything that the DVD tells you. From observing hundreds of teams of new rocketeers over the first four years of UKAYROC, we have learned what common mistakes you need to avoid in this process.

1. Don't over-spend on parts. The basic components of a rocket, such as paper body tubes, balsa fins, and balsa or plastic nose cones are not going to cost you a lot if you design your rocket to use the inexpensive parts that are available from the specialist vendors in the Resources section.
2. Use the right tools. You will need a couple of X-Acto hobby knives with sharp new blades, a steel ruler or straight edge, and various grits of fine sandpaper to build most rocket designs. And you will need a well-lighted work area with a cutting surface. You should not need power tools.
3. Use the right materials in the right places. Body tubes and launch lugs should be commercially-made, smooth, and strong. Don't try using paper towel rolls or other "economy" parts for the main structural member of your rocket, or soda straws for launch lugs. Use balsa wood (or aircraft plywood or basswood) from a hobby store for your fins, probably at least 3mm thickness (for balsa), and make sure that the wood grain lines start on the fin-body glue joint. Put at least a 0.5m long piece of 3mm or 6mm wide sewing elastic in your recovery system as a "shock cord" between the egg section and the main body of the rocket, to absorb the opening shock of the recovery system.
4. Use the right glues. Body parts should be held together with yellow carpenter's wood glue, not white glue. You can use cyanoacrylate "super" glues for repairs, but do not use them for structural construction. You can reinforce fin-body joints with a "fillet" of hobby epoxy if you're worried about fins breaking off.
5. Use the right recovery system. A standard plastic model rocket parachute with 6-8 shroud lines held on using tape discs at the edges of the canopy will not usually work with a heavy model carrying an egg; the plastic will split, or the shroud lines will come off due to the forces of the heavy egg. Use thin nylon parachutes, or thicker plastics, to make the parachute (garbage can liner bag plastic works). For plastic chutes, run the shroud lines over the top of the chute canopy – do



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 14 of 35

not just attach them at the edges. Make sure that you fold the chute carefully (see the Handbook of Model Rocketry on this) and use plenty of non-flammable recovery wadding to protect it from melting together due to the hot gases of the rocket motor ejection charge.



Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 15 of 35

Section 5. ROCKET FLYING

Once your flight vehicle (rocket) is designed and built, it's time for flight test. This section provides some suggestions for organizing and conducting these tests, and for preparing for your single flight attempt at the fly-off. First and foremost, of course, is safety:

Read and follow the UKRA Safety Code (Appendix 2).

1. Launching system. Consider the launching system to be an integral part of the flight vehicle system design, not an afterthought. Of course, the system has to be electrical and incorporate the standoff distance, safety interlock switch, and other requirements of the Safety Code, and it must be on the ground (no balloons!). But it also has to be able to provide the right amount of electrical current and voltage to fire your rocket motor(s) igniter(s), and it must provide rigid guidance to the rocket until it has accelerated to a speed where its fins can properly stabilize it (generally about 15m/s). At the fly-off, an electrical launch system will be provided that can fire a single igniter of any type, and the launching devices provided will be 2m long, 6mm diameter launch rods. If your design requires something different (such as a rail or tower-type launcher), you must bring your own equipment and power source. In any case, you will need to have (or borrow) a system for pre-fly-off test-flying. You may want to have one team member assigned the job of designing and building the launcher, particularly if you do not use a commercially-made "off the shelf" system.

2. Of course, you must follow the UKRA Safety Code and not fly when aircraft are nearby or might be endangered or frightened by your flight! Within the UK it is required to advise the CAA of all rocket launches. The CAA will issue a "Notice to Airmen", commonly called a NOTAM, to advise other air users about the launch. UKRA affiliated rocketry clubs can advise you about NOTAMs or, better still, fly with the clubs as they will already have a NOTAM in place.

The issue of a NOTAM does not remove the responsibility to avoid other air users.

3. Launch Site. The launch site for the Challenge fly-offs is about 300m by 500m of closely-mowed grassland with a few trees. If the winds on the date of the fly-off are fairly light, recovery will be easy; in windy conditions (above 10 miles per hour), rockets that achieve a 45-second duration could drift out of the field. The site you use for pre-fly-off flight testing may or may not be large, but note the minimum site dimensions in the UKRA Safety Code, which depend on the size of the motor(s) in your rocket. The first and most important thing you must have at a launch site is permission from the owner! If your school or organization has a suitable site and supports this event, your problem is easily solved. Otherwise, you must work with local park authorities, private landowners, etc. for permission to use a suitable site. There are generally two concerns expressed by landowners concerning rocket flying:
- a. "It's dangerous". Not true -- the UKRA handout at Appendix 7 summarizes why this is so, and should be used (along with the UKRA Safety Code at Appendix 2) to persuade site owners of this. The accident rate for model rocket flying is nearly zero (exactly zero fatalities), and it is hundreds of times safer than any of the organized athletic events that use similar open fields!



Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 16 of 35

- b. "I'm afraid of the liability (lawsuit) consequences if anything happens". If you are a member of the UKRA, you have personal coverage of up to £5 million against the consequences of an accident that occurs while you are flying, as long as you are following the UKRA Safety Code. See Appendix 6 for more information on this insurance coverage. Your organization, school, school district, or other landowner of your rocket launch site will require liability insurance. Your team can obtain cover for this potential liability by having your supervising teacher/adult and all student members of the team join UKRA.
4. **Launch Safety.** Your rocket (and your launch system, if any) will be inspected for flight safety by an event official before they may be used in the fly-off. Any discrepancies noted there must be corrected before flight is allowed. **AT THE FINALS, YOUR ROCKET MUST HAVE PREVIOUSLY BEEN SUCCESSFULLY TEST-FLOWN.** You must also be prepared to show and explain any complex rocket features affecting flight such as electronic timer systems, etc. The pre-flight safety check will also look for the following types of things:
- Do the motors (or motor) have sufficient thrust (average thrust to liftoff weight ratio 5 or greater) to give the rocket a safe liftoff velocity from its launcher?
 - Is the rocket stable (CG at least one caliber ahead of CP) with motor(s) and egg installed?
 - Are the motor(s) used listed on the UKAYROC Approved Engine List, and are they clearly not modified in any manner by the user?
 - Are the fins and launch lugs attached securely and straight?
 - Is the recovery system (shock cords and anchors, parachute, etc.) sturdy enough to withstand the shock of opening with that rocket, and is it large enough to produce a safe landing speed?
 - Does every separable part of the rocket have a recovery system or a design (e.g. gliding, tumbling) that will ensure it lands at safe, slow speed?
 - Does the design prevent any expended motor casings or other massive objects from being separated in flight without a recovery system?
 - If there is an electronic in-flight recovery control system, does it have a safety/arming technique (switch or safety plug) that positively ensures it is not capable of causing a pyrotechnic event until the rocket has been installed on the launch pad? Hint: If your rocket is complicated, develop a pre-flight checklist and use it before every launch of you rocket. That's what real engineers do!
 - Does the launch system (if the team provides its own) comply with Safety Code requirements for interlocks and standoff distance; can it deliver enough current to ignite multiple motors at once (if cluster ignition is planned); and does the launcher have sufficient length (6 feet is expected) and stiffness (if a launch rod is used, it must be 1/4-inch) to guide the rocket securely until it reaches safe speed?

Important note: Black Powder motors up to D impulse can be transported by road. The requirements for acquiring, storing and transporting Ammonium Perchlorate Composite Propellant (APCP) are complex, and require special licenses from the Police and HSE.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 17 of 35

It is against the law to travel by airliner with rocket motors in your luggage.

We will have a motor vendor available on site at the finals for teams who fly in, and will provide information on how to advance-order fly-off motors from the vendor for onsite delivery.



Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 18 of 35

Section 6. QUALIFYING AND PRACTICE FLIGHTS.

Practice-fly early and often. The teams that qualified to attend the fly-offs in the American competition had an average of 19 practice flights with several crashes and/or lost rockets before they did the flight that got them to the fly-offs. None of them waited until the last week before the deadline to do their first test flight; teams that waited this long were universally unsuccessful. Only by test-flying can you master the skills of recovery system deployment, egg cushioning, and overall flight reliability and repeatability needed for success.

Each team that enters this competition must conduct an UKRA-observed "qualification" flight no later than Sunday, 25th March 2007, and FAX the results of that flight to Space Connections using a copy of the form provided in this Handbook no later than 5 pm on 26th March 2007. Space Connections' fax number is 01274 707611. Plan ahead for weather (rain or wind that "scrubs" a launch day, problems with the rocket's flight, etc.) and do not wait until the last minute to try and fly this flight. Teams must provide their own eggs and timing stopwatches for all qualifying and practice flights; pre-measured eggs and timers with watches will be provided by the UKRA at the fly-offs.

The top ten qualifying teams, based on their reported scores, will be invited to attend the competitive "fly-off" event that will be held on 13th April 2007 at Charterhouse School. All teams who submit a qualification flight form will be notified of their status by 30th March 2007, by Space Connections, and the list of those accepted will be posted at www.UKAYRoC.org.uk. Notification will be sent to you using the email addresses provided on your application.

Selection of the top ten teams will be made on the basis of the lowest (best) scores reported on the qualification flight forms. Score is the total difference (in seconds and hundredths) by which the average timer-measured flight duration differed from 45.00 seconds (always a positive number), plus the total difference (in feet) between the altimeter-reported altitude and 850 feet (always a positive number). Note that cracking of the egg carried by the rocket is disqualifying.

The official qualifying flight must be observed by a senior (adult) member of UKRA, who must be "impartial", i.e. not related to any member of the team and not a paid employee of the school or member of the non-profit organization sponsoring the team. This UKRA observer is one of your two required flight timers. In addition, a second "impartial" person not on the team (who does not have to be a member of the UKRA, or an adult) must be the second flight timer. There are three ways to obtain an UKRA observer, if you do not already know of a qualified local UKRA Senior member who is ready to do this for you:

- a. Attend an organized launch run by an UKRA section, and fly your rocket at that launch. You can also use these launches as a place to practice-fly before you do your official qualification flight. These launches are listed in the "Launch Windows" Calendar on the UKRA web site, www.UKRA.org. Always call a launch's point of contact before attending to confirm the time and place of the launch.
- b. Contact the nearest UKRA affiliated club to see if they have launches not listed on the web site. Check the UKRA site for a list of these clubs and contact information.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC /2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 19 of 35

- c. Contact someone on the list of volunteer "mentors" posted on the UKRA web site (some of these folks live in places remote from a UKRA affiliated club).

Obtaining an observer and providing stopwatches **is the responsibility of each team. PLAN AHEAD**, to find an observer for your qualification flight(s). **DO NOT WAIT** until late March to try to find someone on a day's notice to observe your flight, and do not expect them to drive a long distance to do so. Upon request, we will send you a roster of every senior UKRA member in your area to help you find a nearby qualification observer. Not every UKRA member is aware of the UKAYROC event, so you may have to explain it a bit first when you call one who is not already signed up as a mentor!

If there is no UKRA member available within reasonable distance (and this will be true in a number of areas of the UK), it is OK to have an impartial adult, i.e. someone who is not related to any member of the team and not a paid employee of the team's sponsoring school or member of the team's sponsoring non-profit organization, become a UKRA member in order to be an observer. Experienced rocketeers are certainly preferred to do the observer duties because they can usually understand the rules better and offer advice and tips at the same time -- but experience is not absolutely required. We do not pre-approve observers, but we will check the form they sign to verify that the observer who signs is a current UKRA senior (adult) member.

Finding a launch site is the responsibility of each team, but you do not have to fly at an UKRA launch site. You simply need to locate an open field of suitable size (at least 300m on a side), get permission from the landowner, and comply with any local laws regarding model rocketry. You must arrange for issue of a NOTAM from the CAA. The procedures for doing so are explained here in the Appendix 6. There is a safety handout in Appendix 7 of this Handbook that you should read and can share with concerned landowners and public safety officials.

Teams may practice as much as they wish, but may only make TWO (2) official qualification flight attempts. Both these attempts must be made on the same day. The form provided in this Handbook, or a copy, must be used to report the results of these flights. Be sure to get the signatures of the supervising teacher/adult of the team and the Senior UKRA member who is the official observer. It is the responsibility of the team to fax your completed form for successful qualification flights to Space Connections on 01274 707611 no later than 26th March 2007. UKRA observers who observe a qualification flight attempt that is not successful (i.e. crash or broken egg) are asked to fax the form on that flight to Space Connections.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 20 of 35

2007 QUALIFYING/SELECTION FLIGHT DEMONSTRATION

TEAM'S SCHOOL/ORGANIZATION: _____

UKAYRoC TEAM NUMBER: _____ ADULT ADVISOR: _____

DATE OF THIS FLIGHT: _____ LOCATION: _____

MINIMUM FLIGHT REQUIREMENTS (ALL MUST BE MET) INITIAL IF "YES", OR PUT "NO"

Did this rocket weigh less than 1500 grams at takeoff, with egg and motors? _____

Did this rocket use only motors from the UKAYRoC list of UKRA approved/certified motors? _____

Did the rocket contain one Grade A large, raw hen's egg? _____

Did this rocket make a safe flight and recovery under the UKAYRoC rules & UKRA Safety Code? _____

Did the part of the rocket containing the egg land without any human intervention (catching)? _____

Did the egg carried by the rocket remain uncracked after the flight? _____

SCORING

	Seconds	Hundredths	
Timer #1 (UKRA Observer)		.	
Difference from 45 seconds (no Negatives)		.	A
Timer #1 (Other adult)		.	
Difference from 45 seconds (no Negatives)		.	B
Average time difference = (A + B)/2		.	C
		Feet	
Altitude			
Difference from 850 feet (no Negatives)			D



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 21 of 35

FINAL SCORE

Final score = (C + D) Note: if the answers to any of the questions is “NO” then put “DQ”	
---	--

SUPERVISING TEACHER/ADULT CERTIFICATION

I certify that the student members of this team designed, built, and flew this rocket without my assistance and, to the best of my knowledge, without the assistance of any other adult or any person not on the team. I also certify that no more than two official qualification flight attempts were made by this team, and that the team information on file at Space Connections is current. I understand that team membership can no longer be changed and only team members on file at Space Connections with valid parent consent forms are eligible to receive prizes.

SIGNATURE: _____ PRINT NAME: _____

ADULT UKRA MEMBER OBSERVER CERTIFICATION

I certify that I am a Senior UKRA member who personally observed this flight, and the above initials and scores are mine, based on my observations. I certify that I am not related to any team members or affiliated with their school or non-profit organization, and that this flight was conducted in compliance with the rules of the Team America competition.

SIGNATURE: _____ PRINT NAME: _____

UKRA NUMBER: _____ ADDRESS: _____

PHONE: _____ EMAIL: _____

**UKRA observer to send in form by Fax to Space Connections (01274 707611)
NO LATER THAN 26th March 2007**





UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 22 of 35

Section 7. RESOURCES

This Team Handbook is the most important resource you need to participate in this Challenge. In addition, many answers to questions on contest specifics may be found in the Frequently Asked Questions section at www.UKAYRoC.org.uk There are many resources that may be useful in learning the basic model rocketry skills needed to succeed in this Challenge or in getting the supplies necessary to participate. These include:

The UK Rocketry Association, the largest non-profit model rocket consumer and safety organization. From their website you can link to UKRA's affiliated clubs, for advice and general assistance. www.UKRA.org.uk

Software

Rocksim. RockSIM is approved simulation software for UKAYROC, and information regarding its successful use and other useful rocket design information can be found here. www.apogeerockets.com

SpaceCAD. SpaceCAD is approved simulation software for UKAYROC, and information regarding its successful use and other useful rocket design information can be found here. www.SpaceCAD.com

Books

There are many good books on model rocketry. Particularly noteworthy are:

“The Handbook of Model Rocketry” by G Harry Stine. This is the classic book about model rocketry.

“Model Rocket Design and Construction” by Tim Van Milligan. This book is only available from Apogee Rockets, but is full of constructional advice and tips.

“The Model Rocket Handbook” by Stuart Lodge. A very useful introduction to model rocketry by one of the UK’s leading experts.

Altimeters

Perfectflite:

www.perfectflite.com (USA vendor)



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 23 of 35

UK Specialist Rocketry Vendors

“Rockets and Things”: www.rocketsandthings.com

“Apollo 11 Model Rocketry”: www.apollo.co.uk

“The Rocket Store”: www.rocketstore.co.uk

“Congreve Rockets”: www.rocketmotors.co.uk

Information

“The Rocketry Forum”: www.rocketryforum.com

“Essence Model Rocketry Reviews”: www.rocketreviews.com

“Rocketry Online”: www.rocketryonline.com

The UKRA has developed a nationwide list of experienced rocketeer "mentors" who are willing to be a resource to teams. A "mentor" is an adult rocketry expert advisor who helps a team learn basic rocketry skills and shows them where to get rocket supplies and launch sites. They can do this in person, by phone or e-mail. Teams are not required to have mentors, and mentors are not required to be UKRA-approved (i.e. you can get local help from non-UKRA rocket experts.) There is a list of UKRA-approved mentors on the UKRA website for your convenience.



Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 24 of 35

APPENDIX 1.

RECOMMENDED SCHEDULE OF ACTIVITIES FOR UKAYROC 2007 TEAMS

Week 1-11 below refers to the elapsed time since team entry forms and payment were received and accepted by Space Connections.

WEEK 1

- Ensure all team data (names, e-mail, etc.) on file with SPACE CONNECTIONS is correct
- Join UKRA to obtain insurance (through Space Connections)

WEEK 2

- Assign team responsibilities (such as project manager, airframe, propulsion & ignition, launch system, fundraising etc.)
- Get a mentor (see the list of available UKRA mentors at www.ukra.org.uk)
- Watch the instructional DVD provided as part of your registration materials
- Download the Team Handbook & Rules and the Frequently Asked Questions from the UKAYROC website – www.UKAYRoC.org.uk and have all team members read both
- Begin research on rocket parts supply sources (starting with the suppliers listed in the UKAYROC Handbook)

WEEK 3

- Purchase inexpensive one-stage rocket kit to familiarize team with rocket building & flying, and build it.
- Locate a place to fly rockets or a nearby UKRA launch to attend and fly at. Participating rocketry clubs are listed on www.ukra.org.uk.
- Develop a plan to raise required funds for purchase of rocket supplies (and hopefully for later travel to the fly-offs), covering at least 2-3 rockets and motors for 6-10 test and qualification flights.

WEEK 4

- Obtain a comprehensive book on model rocketry, such as G. Harry Stine's "Handbook of Model Rocketry" from Amazon or your local bookshop. Have all team members read it.
- Obtain either SpaceCAD or Rocksim rocket design and flight simulation computer programs and have team members learn to use it

WEEK 5

- Fly a basic one-stage model rocket

WEEK 6

- Using SpaceCAD or Rocksim and the knowledge gained from reading and from building basic rockets, develop a first design for UKAYROC entry.

WEEK 7

- Using SpaceCAD or Rocksim, conduct flight simulations of your design with various rocket motors on the UKAYROC approved motor list, to determine the best motor(s) to use
- Locate and obtain the materials needed to build your prototype UKAYROC rocket, purchase required parts and rocket motors.



Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 25 of 35

- Obtain two stop-watches for your test-flight program.

WEEK 8

- Design and build the electrical launch system and the launch pad (rod or rail) to be used with your UKAYROC entry, if you do not have a local rocket club's system available for your use

WEEK 9

- Begin construction of your initial design for your UKAYROC entry
- Locate a UKRA Senior (adult) member who can serve as your official observer for your qualification flight(s). This may be through the local UKRA-affiliated rocketry club.

WEEK 10

- Develop a pre-flight checklist for your UKAYROC flight and assign responsibility for each of the duties to a member of the flight team
- Test your launch system by test-firing igniters without installing them in rocket motors

WEEK 11

- Weigh your completed UKAYROC rocket and re-run computer flight simulations with actual rocket weights
- Arrange NOTAMs for your test flights unless you are flying with an UKRA club that already does this for their launches. See the Team Handbook for how to arrange NOTAMs

NO LATER THAN February 1

- Test-fly your initial UKAYROC design (without altimeter), making sure that you leave time to redesign, rebuild, and re-fly if this initial flight/design is not successful!
- If your first flight is fully successful, test-fly again with stopwatch timing and the altimeter installed. Repeat test flights until you hit the design targets.
- If your first flight is not successful, do post-flight failure analysis and re-design.

NO LATER THAN 25 March

- Make your two official qualification flight attempts in front of an UKRA senior member observer

NO LATER THAN 26 March

- Submit (fax) your qualification flight report to be received by SPACE CONNECTIONS no later than this date

On 30th March

- If notified of selection to attend the fly-offs, make reservations for accommodation at the fly-off and conduct fund-raising to cover travel and lodging
- Continue test-flying to "tune" rocket design to target altitude
- If you plan to travel to the fly-off by airline, order rocket motors for fly-off to be shipped to UKAYROC receiving point or delivered on-site by fly-off vendor (Congreve, Rockets & Things)

NO LATER THAN April 2

- Complete and test-fly the actual rocket to be used in the final flyoff (this rocket must have been test-flown before arrival at the flyoff)



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 26 of 35

APPENDIX 2

UK ROCKETRY ASSOCIATION SAFETY CODE

PLEASE VISIT <http://www.ukra.org.uk/safety.html> for the latest version of the safety code.



Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 27 of 35

APPENDIX 3.

UK ROCKETRY ASSOCIATION **ROCKET MOTORS APPROVED FOR USE IN UKAYROC 2007**

The commercially-made model rocket motors listed below have been subjected to rigorous safety and reliability testing conducted by the UKRA Standards & Testing (S&T) Committee and are the only ones approved for sale in the UK for use in this Challenge. All motors listed here are in current production. Every motor listed here will continue to be approved for use in the 2007 event regardless of any subsequent announced changes to the UKRA's overall official engine certification list. This list may be expanded if new motors are certified during the period of the Challenge; this expansion and any revised list will be communicated to all those teams enrolled in the Challenge.

Download "Motor Data Sheets" from the manufacturer's web site if you desire additional information. Each data sheet contains a thrust curve together with values from a test firing, including measured average thrust and total impulse, plus 32 data points for use in altitude simulation computer programs.

<u>Abbreviation</u>	<u>Full Manufacturer Name</u>
Cesaroni	Cesaroni Technology Incorporated
Estes	Estes Industries
Quest	Quest Aerospace Education
Congreve	Congreve Rockets

Note: (R) following the listed casing dimensions denotes that the motor is a reloadable motor system certified only with the manufacturer-supplied casing, closures, nozzle, and propellant. Reloadable motors (and "G" power class motors of any kind) are not available for sale to persons under age 18. Also, the metal casings that reloadable motors use are quite expensive. But if the performance of these types of model rocket motor happens to be exactly what you need for your design, your supervising teacher/adult advisor can purchase them and supervise your use of them.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 28 of 35

UK ROCKETRY ASSOCIATION **ROCKET MOTORS APPROVED FOR USE IN UKAYROC 2007**

As of 17th September 2006

<u>Designation</u>	<u>Mfgr.</u>	<u>Casing</u>	<u>Size</u> (mm)	<u>Propellant</u> (grams)	<u>Total</u> <u>Mass</u>	<u>Impulse</u> (N-sec.)
1/4A3-3T		Estes	13 x 45	0.8		0.62
1/2A3-2T,4T	Estes	13 x 45		2.0	1.25	
1/2A6-2		Estes	18 x 70	2.6		1.25
A3-4T	Estes	13 x 45		3.3	2.50	
A6-4	Quest	18 x 70		3.5	2.50	
A8-3,5		Estes	18 x 70	3.3		2.50
A10-3T,PT	Estes	13 x 45		3.8	2.50	
B4-2,4		Estes	18 x 70	6.0		5.00
B6-2,4,6		Estes	18 x 70	5.6		5.00
B6-0,2,4		Quest	18 x 70	6.5		5.00
C6-0,3,5,7	Estes	18 x 70		10.8	9.0	
C6-0	Quest	18 x 70		11.0	8.8	
C6-3,5		Quest	18 x 70	11.0	8.5	
D11-P	Estes	24 x 70		24.5	18.0	
D12-0,3,5,7	Estes	24 x 70		21.1	17.0	
G69-12A	R	Cesaroni	38 x 125		62.5	128.8
120G40-FS	R	Congreve	29 x 144		60	120
120G60-WS	R	Congreve	29 x 144		60	120
120G70-STD R	R	Congreve	29 x 144	60		120



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 29 of 35

APPENDIX 4.

PERFECTFLITE MAXIMUM ALTITUDE ALTIMETER

Perfectlite Electronics
www.perfectlite.com
PO Box 328, Mirror Lake, NH 03853
(603) 569-1344

DESCRIPTION

The altimeter approved for use in UKAYROC 2007 (the Perfectlite ALT15K/WD Model) is a "maximum altitude altimeter" that precisely measures the air pressure at the altitude where your rocket is located every 0.1 second and convert this to an above-ground altitude value. It is energized by inserting the battery. It senses the liftoff of the rocket from the sudden air pressure drop that results from its altitude change, then senses the maximum altitude that the rocket subsequently reaches, and "freezes" and beeps out this maximum altitude thereafter using a piezoelectric buzzer, until the battery is removed to turn it off. It will not work on flights that achieve less than 160 feet altitude or greater than 15,000 feet altitude (far beyond the 850-foot UKAYROC 2007 target) above ground level. It is accurate to about 1 percent of the measured altitude, which is far better accuracy than any other altitude-measurement technique readily available to hobby rocketeers.

APPROVED ALTIMETERS

Only one altimeter is approved for use in UKAYROC 2007: the Perfectlite ALT15K/WD. It is about 70mm long, fits in an 18mm-diameter body tube like Estes BT-20, weighs 13-14 grams with battery, and uses a 12 volt "N" size lighter battery. Only this UKAYROC-approved altimeter may be used as the basis for official event scores in either local qualification flights or in the final fly-offs.

USING THE ALTIMETER

Read and follow the detailed manufacturer usage instructions provided with the altimeter. Always handle them by the edges when testing or installing to avoid touching any of the circuitry. Never store the device bare in a clear plastic bag; use a small cardboard box, or wrap the altimeter in a paper towel inside a plastic bag. Do not use tape on the altimeter, and use care to keep it clean and dry. Protect it from the fumes and residue created by rocket motors and their ejection charges by installing it in a compartment of your rocket that is totally sealed from motors and charges. Make sure that it cannot "rattle around" in this compartment and get damaged in flight. Always mount the altimeter with the spring end of the battery holder facing upward toward the nose end of the rocket. This will avoid compression of the spring and battery disconnection during a very high acceleration liftoff.



Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 30 of 35

The altitude achieved by the rocket (and the altitude read by the altimeter) depends on launch site altitude and air temperature. If you live at an altitude much different from the Team America launch site (600 feet above sea level), or fly when the temperature much different from the temperature on "fly-off" day in May, your rocket will go to a different altitude (and the altimeter will read a different altitude) than it will at the fly-off. You need to compensate for this in your planning.

An altimeter must be mounted in a "sealed" chamber which must have a vent hole or holes to the outside. A sealed bulkhead below the altimeter chamber is necessary to avoid the vacuum caused by the aft end of a rocket during flight. A sealed bulkhead above the altimeter chamber is necessary to avoid any pressure fluctuations that may be created at the nose end of the rocket. If the front of the payload section slip fits to another section such as a nosecone, then the fit must be as free as possible from turbulence. A breathing hole or vent (also known as a static port) to the outside of the rocket must be in an area where there are no obstacles above it that can cause turbulent air flow over the vent hole. Do not allow screws, ornamental objects, or anything that protrudes out from the rocket body to be in line with and forward of a vent hole. Vents must be neat and burr free and on an outside surface that is smooth and vertical where airflow is smooth without turbulence.

Some rocketeers use multiple static ports (vent holes) instead of just one. Very strong wind blowing directly on a single static port could affect the altimeter. Multiple ports evenly spaced around the rocket tube may help cancel the effects of strong wind on the ground, the effects of transitioning through wind shears during flight, the pressure effects of a non-stable liftoff, or the pressure effects that occur due to flipping and spinning after deployment. If you wish to use multiple ports, then use three or four. Never use two. Ports must be the same size and evenly spaced in line around the tube.

Direct exposure to sunlight will trigger the altimeter pressure sensor and cause it to incorrectly "sense" maximum altitude and beep out a false value before liftoff. Be sure to shade the altimeter from the time you zero it before flight until it is safely inside the altimeter compartment in your rocket.

If the altimeter is reporting an altitude of some very small value (a number less than 160, the launch detect trigger altitude for UKAYROC 2007 altimeters vs 80 feet in previous years) post-flight, this is a result of it getting a brief (approximately 0.1 second) vacuum spike due to a wind gust over the vent hole or other causes. The altimeter would see the altitude going from 0 to over 80 to 160 in 0.1 second (more than 800 feet per second, obviously not a valid reading around apogee) so the spike itself would be excluded from the beeped out apogee reading. Any small number that the altimeter does beep out (4, 8, 12...) would just be the result of background or wind-induced noise.

If direct sunlight shines in the sensor hole, you will get such a spike, though you can exclude this possibility if the altimeter is already shielded inside the rocket and emitting the periodic "ready" chirp.

It is possible (though extremely unlikely) that RF energy from a nearby mobile phone, FRS/GMRS radio, etc could cause such a spike. The altimeter does have RF bypassing to reduce such effects, but a full power



Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 31 of 35

GMRS radio held about an inch away from the altimeter could trigger it.

Another much more likely possibility is that of wind gusts triggering the altimeter as it sits on the pad. If a wind gust creates a brief vacuum in the compartment that exceeds the equivalent vacuum of the launch detect altitude, then the altimeter will be triggered and will report a small number as the vacuum bleeds out.

There are ways to minimize this effect. The size of the sampling hole depends on the altimeter compartment dimensions, but generally should be quite SMALL. There is a table in the manual, and for most UKAYROC sized rockets a 1.5mm or smaller hole is proper. Many people seem to be drilling a nice large 6mm hole in the side of their rocket, which not only isn't necessary, but will increase wind noise on the data. It will also increase the likelihood and magnitude of spikes in the data when the rocket separates, which can affect the apogee reading. Since the goal of the contest is consistency, clean data is essential. In order to get the cleanest data, the sampling holes should NOT be oversized, and ejection should be slightly after apogee so any turbulence-induced noise on the data will not spike up over the true apogee height.

The altimeter manual should be followed regarding size and placement of sampling holes. In addition to the proper size (about 1.5mm) and placement (3X body tube diameter back from the nosecone) it is also recommended in the manual that multiple holes be used around the circumference to minimize the effects of gusts blowing across the rocket. The best configuration would be four 0.75mm holes (1/4 the area of the single 1.5mm hole) spaced at 90 degree intervals around the circumference of the body tube. This will reduce the likelihood of false triggering and insure the cleanest, most consistent data.

If the altimeter remains silent post-flight, there are a number of possibilities. First is a weak battery. Battery voltage must be at least 11 volts. Second are dirty battery contacts or battery holder contacts. If the altimeter starts beeping again when the battery is rotated a turn or two in the battery holder it would indicate that the contacts were dirty. Clean with an eraser and blow out debris. Third is that the battery lost contact briefly during flight (shock at motor ignition or ejection are the most likely times, especially if the altimeter is free-floating in a compartment and can slam around). The altimeter should be padded to protect it from shock, the battery holder should be inspected for cracks from previous crashes which could loosen the battery retention force, and the altimeter should be installed with the spring end of the battery holder facing "up" so the spring is not compressed during acceleration. While it shouldn't be necessary, a wrap of tape around the battery holder can prevent deformation, especially if the holder is cracked.

If the altimeter is still beeping the launch ready chirp on landing, this is almost without question a case of the altimeter losing power during flight. It detected launch, started recording the flight, then lost power momentarily during flight (again, shock from boost, ejection, etc breaking battery contact). It would then start over from scratch, waiting thirty seconds and beep awaiting launch. But since the rocket would be on its way down by then, another launch detect would never get triggered, so it would still be beeping readiness on the ground.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 32 of 35

APPENDIX 5.

CIVIL AVIATION AUTHORITY NOTAM PROCEDURES

It is a Civil Aviation Authority (CAA) requirement that all air users should be advised of unusual air activities that might be hazardous. This includes model rocket launches. The process for notifying air users is called the “Notice to Airmen” or NOTAM. This appendix tells you how to request a NOTAM.

NOTAMs are requested 28 days before the event by sending an email to ausops@dap.caa.co.uk. The email follows a specific format which is summarized below:

- A. School 250605
- B. Anytown. Grid Ref SX5678. 1 mile radius.
- C. 0606251000 local
- D. 0606251700 local
- E. Model rocket flying. Surface to 1500 ft. POC Fred Smith 07711 123123.

Decode of their automatic input format:

Line A: Reference number, user defined

Line B: Location in text and 4-figure grid reference or lat-long

Line C: YY MM DD time for start. Add "local" otherwise they assume GMT.

Line D: YY MM DD time for finish

Line E: Activity and requested airspace, Ask for what you really need and don't overstate it. Contact number should be someone onsite that pilots can talk to.

The email should be sent to ausops@dap.caa.co.uk and titled "NOTAM Request". If you want to talk to the cell for advice telephone 0207 453 6589.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 33 of 35

APPENDIX 6.

UKRA ROCKET-FLYING INSURANCE FREQUENTLY-ASKED QUESTIONS

The following information is produced from relevant sections of the BMFA Member's Handbook.

The primary insurance cover provided by the BMFA for its members is Third party, Public and Products Liability. In addition, a 'no fault' personal accident insurance covering major disablement is included.

TITLE.

It covers the BMFA, its employed, elected and co-opted officers, their committees and all registered clubs and individual members of the BMFA.

ACTIVITIES.

It covers the normal and lawful pursuits of the Association and its registered members.

INDEMNITY LIMITS FOR THE THIRD PARTY PUBLIC AND PRODUCTS LIABILITY.

£5,000,000 any one accident, unlimited for period of insurance, subject to a £20 property damage excess.

MODELS COVERED.

Models powered by approved solid fuel rocket propulsion systems up to and including 'M' size motors.

EXTENSIONS.

- (a) Member-to-Member liability is covered including damage to property belonging to fellow members but generally excluding damage to models, radio equipment, tools etc.
- (b) Indemnity is automatically extended to any principals (Landowners, Schools, Local Authorities, Government Departments etc.) whose land or premises is used by any BMFA affiliated club or registered member.
- (c) The indemnity is extended to the committee members of any affiliated club and all lawful club activities are indemnified.
- (d) The reduced rate insurance cover available to juniors under the schools and Youth Groups membership scheme only applies when such juniors are flying under the supervision of their group leader(s). To obtain full unlimited BMFA insurance cover, any such junior must become a full junior member of the BMFA.
- (f) In the BMFA Airside Cover special provision, indemnity is provided for members operating their private motor vehicle 'airside' on an airfield or aerodrome, in pursuit of any activity associated with model flying where the member's own private motor vehicle policy makes a specific exclusion in this respect. A higher excess is applicable to any claim made under this special provision.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 34 of 35

CONDITIONS.

- (a) You must not, under any circumstances, admit liability or make or agree any financial settlement with respect to any incident which might give rise to a claim under the policy.
- (b) It is the duty of the insured to at all times exercise reasonable care to see that their models are sound and in proper order and that all reasonable safeguards and precautions against accidents are provided and used.

INCIDENT REPORTING PROCEDURES.

- (a) Prompt notification of all incidents / accidents that may result in a claim on the policy is essential. Initial telephone contact with the BMFA's Leicester office should be within 24 hours of the incident. Reports out of hours will be recorded on the office answer phone.
- (b) The Leicester office will supply you with an incident report form which will become the basis of an initial report of an incident to the Insurer if required. The office staff will give you any specific advice you need to help you complete this form.
- (c) Regardless of how serious an incident might be, the reporting procedure outlined above will nearly always be adequate. If the incident is very serious, and external Authorities are involved, they will have their own emergency procedures for contacting the Association. You should still follow the normal reporting procedure.

OPERATIVE DATES.

The basic public liability cover is effective from the date of joining until the end of the current membership year. Note that date of joining means the date that payment is made.

CERTIFICATES.

Individual insurance certificates will be provided to all registered members of the Association from the Leicester office with your membership card.

PERSONAL ACCIDENT SCHEME.

Members of the BMFA are covered by a standard personal accident policy whilst participating in Association activities which include the building and flying of model rockets for sport and recreational purposes.

The benefits payable under the policy are £5,000 in respect of accident death and up to £25,000 for permanent disability; however, the level of benefits payable may change from time to time.

In addition to the above benefits the Association has been able to negotiate a special additional provision within the policy conditions which provides for a benefit to be payable for a range of other major injuries. Payments under this section of the policy are established as a percentage of the Capital Benefit for permanent disablement in force at the time a qualifying injury occurs. Again the scope and level of benefits payable under this special provision may change from time to time. The Association will retain a composite listing of the percentage payments payable for each category of major injury and will notify members of any changes through BMFA News.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 35 of 35

APPENDIX 7.

United Kingdom Rocketry Association.

MODEL ROCKETRY: THE WORLDS SAFE, EDUCATIONAL AEROSPACE HOBBY

WHAT IS MODEL ROCKETRY?

Model rocketry is aerospace engineering in miniature. This popular hobby and educational tool was founded in 1957 to provide a safe and inexpensive way for young people to learn the principles of rocket flight. It has grown since then to a worldwide hobby with over 5 million flights per year, used in some 30,000 schools worldwide. Its safety record is extraordinarily good, especially compared to most other outdoor activities, and its safe and inexpensive products are available in some model shops and dedicated vendors in the US, Europe and more importantly the UK. Model rocketry has inspired at least two generations of young people to pursue careers in technology.

They are always designed to be recovered and flown many times, with the motor being replaced between flights.

Model rockets come in two size classes: **LOW POWER** rockets, which are less than 500 gram in weight (1500 gram under some conditions), have less than 62.5 gram (125 gram under some conditions) of propellant, and generally available to consumers of all ages; and **HIGH-POWER** rockets, which are larger, use motors larger than “G” power, and are available only to adults.

WHAT IS A MODEL ROCKET?

A model rocket is a reusable, lightweight, non-metallic flight vehicle that is propelled vertically by an electrically-ignited, commercially-made, certified, and non-explosive solid fuel rocket motor. Beside very important safety reasons, it is illegal for any rocket hobbyist to mix, load chemicals or manufacture raw propellant; all model rocket motors are bought pre-made, including reusable casing type systems. Model rockets are always designed and built to be returned safely and gently to the ground with a recovery system such as a parachute.

ARE THESE ROCKETS LEGAL?

Model rockets may be legally flown provided that the entire flight starts and finishes land for which the landowner has given permission. Flights may be made in uncontrolled airspace, which is away from airfields. The guiding principle is that model rockets must not cause a hazard to other air users. This is amplified in the Air Navigation Order and CAA publication CAP 658. Flights should not be made in mountainous areas or on estuaries, as the rockets could be confused with emergency flares causing an inadvertent call-out of the rescue services.



UK Aerospace Youth Rocketry Challenge
www.UKAYRoC.org.uk

Document Ref:	UKAYRoC/2007 Handbook/Reference/Doc
Date Issued:	2 nd November 2006
Version:	Final
Page:	Page 36 of 35

IS THIS HOBBY SAFE?

In well over 250 million flights since the founding of the hobby, there has never been a death caused by the flight of a model rocket. Injuries are rare and generally minor. They are almost always the result of failure to follow the basic safety precautions and instructions provided by the manufacturers. Model rocketry's record shows that it is safer than almost any model or other outdoor physical activity.

The hobby operates under the simple and easy-to-follow Model Rocket and High-Power Rocket Safety Codes of the United Kingdom Rocketry Association, which have been fine-tuned by professional engineers and public safety officials to maximize user and spectator safety. The foundations of these Safety Codes are that model rockets must be electrically ignited from a safe distance with advance warning to all those nearby, must have recovery systems, must be flown vertically in a suitably-sized field with no aircraft in the vicinity, and must never be aimed at a target or used to carry a pyrotechnic payload. All model rocket motors are subjected to extensive safety and reliability certification testing to strict HSE guidelines and European standards.

AREN'T THESE ROCKETS FIREWORKS?

All HSE and European guidelines recognize model rockets as different from fireworks. Fireworks are single-use recreational products designed solely to produce noise, smoke, or visual effect. They have few of the designed-in safety features or pre-consumer HSE safety testing of a reusable model rocket, and none of the model rocket's educational value.

Fireworks are fuse-lit, an inherently dangerous ignition method that is specifically forbidden in the hobby of model rocketry. Model rockets are prohibited from carrying any form of pyrotechnic payload; their purpose is to demonstrate flight principles or carry educational payloads, not blow up, make noise, or emit a shower of sparks.

WHO ARE THE EXPERTS?

The oldest and largest organization of model rocketeers in the UK is the United Kingdom Rocketry Association (UKRA). This non-profit organization represents the hobby to public safety officials and legislative agencies, playing a key role in maintaining the safety of the hobby and safety code development. The UKRA also has its own web site, runs national model rocketry events, competitions, and offers liability insurance coverage through BMFA for model rocketeers. You may reach the UKRA at:

UKRA
 Post Office Box 1561
 Sheffield S11 7XA
www.UKRA.org.uk

You may download copies of the UKRA handbook here.

<http://www.ukra.org.uk/membership/documentation.html>

And the UKRA safety code here.

www.ukra.org.uk/safety.html

